



Product Service

# CERTIFICATE

No. Z1A 17 12 90361 007

**Holder of Certificate:** Kinnarps ABIndustrigatan 1  
521 88 Kinnarp  
SWEDEN**Factory(ies):** 90361**Certification Mark:****Product:** Office chair  
Office work chairs**Model(s):** Plus [6]  
Models: 6770, 6772, 6774, 6780, 6782, 6784**Parameters:**  
Overall width: 615 mm  
Overall depth: 615 mm  
Overall height, low backrest: 920 mm  
Overall height, high backrest: 965 mm  
Material:  
Seat and backrest: Plastic and metal frame  
moulded in foam  
Armrests : Arm 2: TPU/TPU, Arm 4: Technogel/TPU  
Under frame: Aluminium star baseThe office work chairs Plus [6], models: 6770, 6772, 6774,  
6780, 6782, 6784 correspond to type A.

Further parameters see attachment.

**Tested according to:** DIN EN 1335-1:2002  
DIN EN 1335-2:2010  
DIN EN 1335-3:2009  
AfPS GS 2014:01 PAK

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 713115323**Valid until:** 2022-12-12**Date,** 2017-12-14

( Jens Biesenack )

Page 1 of 2





Further parameters:

Model	6770	6772	6774	6780	6782	6784
<b>SEAT</b>						
seat height	400 – 525 mm	400 – 525 mm	400 – 525 mm	400 – 525 mm	401 – 539 mm	400 – 525 mm
seat depth	400 – 470 mm	400 – 470 mm	400 – 470 mm	400 – 470 mm	398 – 460 mm	400 – 470 mm
depth of the seat surface	450 mm	450 mm	450 mm	450 mm	460 mm	450 mm
seat width	430 mm	430 mm	430 mm	430 mm	456 mm	430 mm
inclination of seat surface	3,7° until -13,7°	3,7° until -13,7°	3,7° until -13,7°	3,7° until -13,7°	-2° until -11°	3,7° until -13,7°
<b>BACKREST</b>						
height of the back supporting point S above the seat surface	165 – 260 mm	165 – 260 mm	165 – 260 mm	165 – 260 mm	170 – 270 mm	165 – 260 mm
height of the back pad	620 mm	620 mm	620 mm	685 mm	690 mm	685 mm
height of the upper edge of the backrest relative to point A	535 – 630 mm	535 – 630 mm	535 – 630 mm	560 – 650 mm	580 – 672 mm	560 – 650 mm
width of the backrest	400 mm	400 mm	400 mm	400 mm	410 mm	400 mm
horizontal radius of the backrest at point S	>400 mm	>400 mm	>400 mm	>400 mm	>400 mm	>400 mm
backrest inclination	17,4°	17,4°	17,4°	17,4°	23°	17,4°
<b>ARMREST (optional)</b>						
length of the armrest	-	220 mm	250 mm	-	230 mm	250 mm
width of the armrest	-	70 mm	100 mm	-	90 mm	100 mm
height of the armrests above the seat	-	180 – 300 mm	200 – 230 mm	-	178 – 288 mm	200 – 230 mm
distance from the front of the armrests to the front edge of the seat surface	-	>100 mm	>100 mm	-	115 – 186 mm	>100 mm
clear width between the armrests	-	430 – 510 mm	430 – 510 mm	-	410 – 510 mm	430 – 510 mm
<b>UNDERFRAME</b>						
maximal offset of the underframe (anti-stumbling-dimension)	345 mm	345 mm	345 mm	345 mm	362 mm	345 mm
stability dimension	235 mm	235 mm	235 mm	235 mm	230 mm	235 mm